



---

Engine Make:	Engine Model:	Part Number:
<b>mitsubishi</b>	<b>4G63 EVO 1-3</b>	<b>1-SLX282</b>
Valve Clearance:	Intake: <b>0.20mm</b> Set <b>COLD</b> at the <b>CAM</b>	Exhaust: <b>0.20mm</b> Set <b>COLD</b> at the <b>CAM</b>
Cam Lift:	Intake: <b>6.85mm</b>	Exhaust: <b>6.85mm</b>
Rocker Ratio:	Intake: <b>1.73</b>	Exhaust: <b>1.73</b>
Nett Valve Lift:	Intake: <b>11.50mm</b>	Exhaust: <b>11.50mm</b>
Advertised Duration @ <b>0.10mm</b>	Intake: <b>282</b>	Exhaust: <b>288</b>
Duration @ <b>1.00mm VALVE LIFT</b>	Intake: <b>240</b>	Exhaust: <b>244</b>
Timing @ <b>1.00mm VALVE LIFT</b>	IVO: <b>11 BTDC</b>	EVO <b>58 BBDC</b>
	IVC: <b>49 ABDC</b>	EVC <b>6 ATDC</b>
	Intake: <b>109 ATDC</b>	Exhaust: <b>116 BTDC</b>
	Intake: <b>2.04mm</b>	Exhaust: <b>1.35</b>

---

[www.kelfordcams.com](http://www.kelfordcams.com)

[sales@kelfordcams.com](mailto:sales@kelfordcams.com)